FORMALDEHYDE & AMINO RESINS

VIORARES UF

Urea Formaldehyde (UF) Powder Resin

Product description

Thermosetting amino resin with high reactivity and good cost-performance for wood-based panels.

Typical properties

Property	Typical value
CAS no.	9011-05-6
Appearance	White to off-white powder
Grades	Six grades for MDF, particleboard, plywood and laminating

Main applications

- Adhesive for MDF, particleboard and chipboard
- Hardwood plywood
- Lamination
- Foundry sand moulds
- Wrinkle-resistant textile finishes

Packaging & supply

Bulk, ISO tank, flexitank, IBC, drums, bags or big bags depending on the product. CIF / CFR European ports or DAP / DDP delivered. Lead time and MOQ on request.

Documents

Safety Data Sheet (REACH/CLP format), Certificate of Analysis per batch and full guaranteed specification available on request.

Values are typical and indicative only and do not constitute a guaranteed specification.
Guaranteed specification, Certificate of Analysis and Safety Data Sheet are provided with each quotation.