FORMALDEHYDE & AMINO RESINS

VIORARES MUF

Melamine Urea Formaldehyde (MUF) Powder Resin

Product description

Amino resin with higher water and weather resistance, suited to panels for exterior or high-humidity use.

Typical properties

Property	Typical value
CAS no.	25036-13-6
Appearance	White powder
Grades	Three grades with different melamine contents; tailor-made on request

Main applications

- Laminated veneer lumber (LVL)
- Moisture-resistant particleboard and MDF
- Exterior plywood

Packaging & supply

Bulk, ISO tank, flexitank, IBC, drums, bags or big bags depending on the product. CIF / CFR European ports or DAP / DDP delivered. Lead time and MOQ on request.

Documents

Safety Data Sheet (REACH/CLP format), Certificate of Analysis per batch and full guaranteed specification available on request.

Values are typical and indicative only and do not constitute a guaranteed specification.
Guaranteed specification, Certificate of Analysis and Safety Data Sheet are provided with each quotation.