NORMAL PARAFFINS & ALKYLATES

Heavy Alkyl Benzene (HAB)

Product description

Heavy alkylate raw material for lubricant additives, dielectric fluids and heat transfer applications.

Typical properties

Property	Typical value
Appearance	Straw yellow liquid
Heavy alkylate, %	99.5 min
LAB content, %	0.5 max
Water, ppm	100 max
ASTM color	1.5 max

Main applications

- Feedstock for lube and fuel additive sulfonates
- Heat transfer and insulating fluids
- Transformer dielectric fluids
- Refrigeration compressor lubricants
- Greases and synthetic lubricants
- Enhanced oil recovery surfactants

Packaging & supply

Bulk, ISO tank, flexitank, IBC, drums, bags or big bags depending on the product. CIF / CFR European ports or DAP / DDP delivered. Lead time and MOQ on request.

Documents

Safety Data Sheet (REACH/CLP format), Certificate of Analysis per batch and full guaranteed specification available on request.

Values are typical and indicative only and do not constitute a guaranteed specification.
Guaranteed specification, Certificate of Analysis and Safety Data Sheet are provided with each quotation.