SPECIALTY SURFACTANTS & ADDITIVES

Di-Alkyl Benzene Sulfonic Acid (DABSA)

Product description

Anionic sulfonic acid intermediate for oil-soluble metallic sulfonates.

Typical properties

Property	Grade 450	Grade 460
Active matter, wt%	70-75	80-85
Total acid number, mg KOH/g	114 max	97-110
Water, wt%	0.5 max	0.5 max
Molecular weight	450	460

Main applications

- Calcium, magnesium, sodium, barium and polyamine sulfonates
- Automotive and engine oil additives
- Metalworking, coatings and grease

Packaging & supply

Bulk, ISO tank, flexitank, IBC, drums, bags or big bags depending on the product. CIF / CFR European ports or DAP / DDP delivered. Lead time and MOQ on request.

Documents

Safety Data Sheet (REACH/CLP format), Certificate of Analysis per batch and full guaranteed specification available on request.

Values are typical and indicative only and do not constitute a guaranteed specification.
Guaranteed specification, Certificate of Analysis and Safety Data Sheet are provided with each quotation.