PROCESS OILS & OILFIELD

VIORATRANS IEC

Transformer Oil (IEC 60296)

Product description

Insulating oil for transformers and electrical equipment, uninhibited and inhibited grades.

Viora grades: VIORATRANS IEC-U, VIORATRANS IEC-I

Typical properties

Property	Uninhibited	Inhibited
Appearance	Clear & bright	Clear & bright
Specific gravity @ 15 °C	< 0.895	< 0.895
Kinematic viscosity @ 40 °C, cSt	< 12	< 12
Flash point, °C	> 135	> 135
Pour point, °C	< -40	< -40

Main applications

- Power and distribution transformers
- Switchgear and electrical equipment

Packaging & supply

Bulk, ISO tank, flexitank, IBC, drums, bags or big bags depending on the product. CIF / CFR European ports or DAP / DDP delivered. Lead time and MOQ on request.

Documents

Safety Data Sheet (REACH/CLP format), Certificate of Analysis per batch and full guaranteed specification available on request.

Values are typical and indicative only and do not constitute a guaranteed specification.
Guaranteed specification, Certificate of Analysis and Safety Data Sheet are provided with each quotation.